



S-1140/41

S-1145/46

Ancho cara a cara
ISO 5752 serie 14
EN 558-1 serie 14

Conexión PN16/10

* Taladrado 4 agujeros




por tipos S1140/41

Válvulas de compuerta, con cuadrillo de maniobra, desmontable en carga

PFA 16 bar

Ejecución corta DN	EPDM - T° max 90°		NITRILE - T° max 70°	
	S-1140	S-1141	S-1145	S-1146
40 PN16	149L 075 400	149L 076 700	149L 134 900	149L 139 600
50 PN16	149L 075 500	149L 076 800	149L 135 000	149L 139 700
60/65 PN16	149L 075 600	149L 076 900	149L 135 100	149L 139 800
80 PN10*	149L 075 800	149L 077 100	149L 135 300	149L 140 000
80 PN16	149L 075 700	149L 077 000	149L 135 200	149L 139 000
100 PN16	149L 012 300	149L 012 400	149L 135 400	149L 140 100
125 PN16	149L 075 900	149L 077 200	149L 135 500	149L 140 200
150 PN16	149L 076 000	149L 077 300	149L 135 600	149L 140 300
200 PN10	149L 076 100	149L 077 400	149L 135 700	149L 140 400
200 PN16	149L 076 200	149L 077 500	149L 135 800	149L 140 500
250 PN10	149L 076 300	149L 077 600	149L 135 900	149L 140 600
250 PN16	149L 076 400	149L 077 700	149L 136 000	149L 140 700
300 PN10	149L 076 500	149L 077 800	149L 136 100	149L 140 800
300 PN16	149L 076 600	149L 077 900	149L 136 200	149L 140 900
400 PN10	149L 010 200	149L 064 300	149L 133 000	149L 139 200
400 PN16	149L 010 300	149L 064 400	149L 139 100	149L 139 300

DATOS TÉCNICOS



Tipos
S-1140/41
S-1145/46

DN	H mm	L mm	Kg
40	181	140	6
50	211	150	9
65	243	170	12
80	330	180	22
100	324	190	23
125	418	200	33
150	420	210	38
200	536	230	60
250	639	250	86
300	728	270	128
400	1053	310	285

Estas válvulas se pueden preparar para el montaje de un actuador neumático o eléctrico. Consultarnos para el suministro de los actuadores o para el tipo de indicador de posición o microcontacto.

S1140V/41V

S1145V/46V

Ancho cara a cara
ISO 5752 serie 14
EN 558-1 serie 14

Conexión PN16/10

* Taladrado 4 agujeros



por tipos S1140V/41V

Válvulas de compuerta con volante desmontable en carga

PFA 16 bar

Ejecución corta DN	EPDM - T° max 90°		NITRILE - T° max 70°	
	S-1140V	S-1141V	S-1145V	S-1146V
40 PN16	149B 012 817	149B 012 833	149B 015 991	149B 016 007
50 PN16	149B 012 818	149B 012 834	149B 015 992	149B 016 008
60/65 PN16	149B 012 819	149B 012 835	149B 015 993	149B 016 009
80 PN10*	149B 012 821	149B 012 837	149B 015 995	149B 016 011
80 PN16	149B 012 820	149B 012 836	149B 015 994	149B 016 010
100 PN16	149B 012 822	149B 012 838	149B 015 996	149B 016 012
125 PN16	149B 012 823	149B 012 839	149B 015 997	149B 016 013
150 PN16	149B 012 824	149B 012 840	149B 015 998	149B 016 014
200 PN10	149B 012 826	149B 012 842	149B 015 999	149B 016 015
200 PN16	149B 012 825	149B 012 841	149B 016 000	149B 016 016
250 PN10	149B 012 828	149B 012 844	149B 016 001	149B 016 017
250 PN16	149B 012 827	149B 012 843	149B 016 002	149B 016 018
300 PN10	149B 012 830	149B 012 846	149B 016 003	149B 016 019
300 PN16	149B 012 829	149B 012 845	149B 016 004	149B 016 020
400 PN10	149B 012 832	149B 012 848	149B 016 005	149B 016 021
400 PN16	149B 012 831	149B 012 847	149B 016 006	149B 016 022

DATOS TÉCNICOS



Tipos
S-1140V/41V
S-1145V/46V

DN	H mm	L mm	Kg
40	181	140	7
50	211	150	10
65	243	170	13
80	330	180	24
100	324	190	25
125	418	200	35
150	420	210	40
200	536	230	66
250	639	250	94
300	728	270	140
400	1053	310	285

Consultarnos para modelo con indicador de posición o microcontacto

S-1240/41

S-1245/46

Ancho cara a cara
ISO 5752 serie 15
EN 558-1 serie 15

Conexión PN16/10

* Taladrado 4 agujeros




por tipos S1240/41

Válvulas de compuerta, con cuadrillo de maniobra, desmontable en carga

PFA 16 bar

Ejecución larga DN	EPDM - T° max 90°		NITRILE - T° max 70°	
	S-1240	S-1241	S-1245	S-1246
40 PN16	149L 078 500	149L 079 800	149L 145 200	149L 146 600
50 PN16	149L 078 600	149L 079 900	149L 145 300	149L 146 700
60/65 PN16	149L 078 700	149L 080 000	149L 145 400	149L 146 800
80 PN10*	149L 078 900	149L 080 200	149L 145 600	149L 147 000
80 PN16	149L 078 800	149L 080 100	149L 145 500	149L 146 900
100 PN16	149L 018 700	149L 018 800	149L 145 700	149L 147 100
125 PN16	149L 079 000	149L 080 300	149L 145 800	149L 147 200
150 PN16	149L 079 100	149L 080 400	149L 145 900	149L 147 300
200 PN10	149L 079 200	149L 080 500	149L 146 000	149L 147 400
200 PN16	149L 079 300	149L 080 600	149L 146 100	149L 147 500
250 PN10	149L 079 400	149L 080 700	149L 146 200	149L 147 600
250 PN16	149L 079 500	149L 080 800	149L 146 300	149L 147 700
300 PN10	149L 079 600	149L 080 900	149L 146 400	149L 147 800
300 PN16	149L 079 700	149L 081 000	149L 146 500	149L 147 900
400 PN10	149L 184 700	149L183 500	149L 183 900	149L 184 300
400 PN16	149L 184 800	149L183 600	149L 184 000	149L 184 400
500 PN10	149L 159 700	149L184 900	149L 184 100	149L 184 500
500 PN16	149L 159 800	149L185 000	149L 184 200	149L 184 600

DATOS TÉCNICOS



Tipos
S-1240/41
S-1245/46

DN	H mm	L mm	Kg
40	181	240	7
50	211	250	10
65	243	270	13
80	330	280	23
100	324	300	25
125	418	325	33
150	420	350	42
200	536	400	76
250	639	450	101
300	728	500	136
400	1043	600	430
500	1043	700	480

Consultarnos para modelo con indicador de posición o microcontacto